

DNA60-12

POLYCRYSTALLINE MODULE



KEY FEATURES



12 Busbar Solar Cell

Stronger current collection ability, Special circuit design with much lower hot spot temperature;



Module efficiency up to 17.41%

Higher power brings lower kilowatt-hour cost, higher lifetime generating capacity, simultaneously lower annual power attenuation;



PID Resistant

Excellent PID resistance at 96 hours (85°C/85%) test, and also can be improved to meet higher standards for the particularly harsh environment;



Low-Light Performance

Excellent power generation performance under Low-Light condition due to 12 busbar;



Anti-Crack

Excellent anti-microcracking performance with more balanced interior stress;



Strength and Durability

Certified for 5400Pa snow and 2400Pa loads test;



System Certification


ISO 9001:2008

ISO 14001:2004

OHSAS 18001:2007

Linear Performance Warranty


10 Year Product Warranty • 25 Year Linear Power Warranty




DNA SOLAR Introduction

DNA SOLAR is the world's leading green energy provider, committed to making clean energy illuminate every corner of the world. We strive to provide high-efficiency, high-quality and low-cost clean energy solutions. DNA SOLAR insists on continuous innovation around customer needs. We invest heavily in technology research, and promotes green energy in the world.

Engineering Drawings



I-V CURVE (280W)



Electrical Specifications (STC)

Model	DNA60-12-280P	DNA60-12-285P	DNA60-12-290P
Maximum Power (Pmax)	280	285	290
Power Tolerance (W)	0~+5	0~+5	0~+5
Open Circuit Voltage (Voc)	39.18	39.32	39.55
MPP Voltage (Vmp)	31.39	31.58	31.68
Short Circuit Current (Isc)	9.45	9.55	9.65
MPP Current (Imp)	8.92	9.03	9.24
Module Efficiency (%)	17.10	17.41	17.71

Mechanical Specifications

Model	Data
Cell Type	12BB Poly 156.75×156.75mm
No. of Cells	60(6×10)
Dimensions	1650×992×35mm
Weight	19kg
Glass	3.2mm, Low Iron Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67/IP68, 3 diodes
Output Cables	4mm², Length 900mm
Connector type	MC4 compatible

Temperature Specifications

Item	Data
NOCT	45°C ±2°C
Temperature Coefficient (Pmax)	-0.40%/K
Temperature Coefficient (Voc)	-0.31%/K
Temperature Coefficient (Isc)	0.06%/K

Operating Condition	Data
Maximum System Voltage	1000V/1500 VDC(TÜV)
Operating Temperature	-40°C+85°C
Maximum series fuse rating	15A

Packaging Specifications

Packing unit	30pcs.(35mm)
Modules per 40'HQ container	30pcs.(35mm)

Remark

Tolerance	±3%(Vmp, Imp, Voc, Isc)
STC	Irradiance 1000W/m², Cell Temperature 25°C, AM1.5